Revision: 22.11.2021

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2021

Version number 11 (replaces version 10)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name BITUMINOUS SEALING COATING 2 K STANDARD COMP.B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Bitumen high build coating
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Cement portland, Low-chromate according to EU-VO 1907/2006 (REACH)

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust.

P280 Wear protective clothing / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

(Contd. on page 2)

Printing date 22.11.2021 Version number 11 (replaces version 10) Revision: 22.11.2021

Trade name BITUMINOUS SEALING COATING 2 K STANDARD COMP.B

(Contd. of page 1)

P332+P313 If skin irritation occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture consisting of the following components with harmless additives.

Dangerous components:

CAS: 65997-15-1 | Cement portland, Low-chromate according to EU-VO 1907/2006 | 50-100% | EINECS: 266-043-4 (REACH)

♠ Eye Dam. 1, H318

🄥 Skin Irrit. 2, H315; STOT SE 3, H335

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing

In case of persistent symptoms consult doctor.

Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies.
- 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 3)

Printing date 22.11.2021

Version number 11 (replaces version 10)

Trade name BITUMINOUS SEALING COATING 2 K STANDARD COMP.B

(Contd. of page 2)

Revision: 22.11.2021

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Thorough dedusting.

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of dust.

- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: Store only in the original container.
- · Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

· Further information about storage conditions:

Keep container tightly sealed.

Store under dry conditions.

- · Storage class 13
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Components with critical values that require monitoring at the workplace:

65997-15-1 Cement portland, Low-chromate according to EU-VO 1907/2006 (REACH)

WEL Long-term value: 10* 4** mg/m3 *inhalable dust **respirable dust

· Additional information: The lists that were valid during the compilation were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Breathing protection recommended.

Filter P2.

- · Hand protection Protective gloves.
- · Material of gloves

Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Tightly sealed safety glasses.

(Contd. on page 4)

Printing date 22.11.2021 Version number 11 (replaces version 10) Revision: 22.11.2021

Trade name BITUMINOUS SEALING COATING 2 K STANDARD COMP.B

(Contd. of page 3)

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Grey
· Smell: Light
· Melting point/freezing point: n.a. °C

Boiling point or initial boiling point and

boiling range Not determined Not applicable

Self-inflammability: Product is not selfigniting.

· Solubility

• Water: Soluble • Steam pressure at 20 °C: n.a. hPa

· Density and/or relative density

Density at 20 °C 1.3 g/cm³

· 9.2 Other information

· Appearance:

· Form: Powder

· Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** n.a. °C

• Explosive properties: Product is not explosive.

· Information with regard to physical hazard classes

Explosives Void · Flammable gases Void Aerosols Void Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void flammable gases in contact with water Void

Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void Void Void Void Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 5)

Printing date 22.11.2021 Version

Version number 11 (replaces version 10)

Trade name BITUMINOUS SEALING COATING 2 K STANDARD COMP.B

(Contd. of page 4)

Revision: 22.11.2021

· 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification:

65997-15-1 Cement portland, Low-chromate according to EU-VO 1907/2006 (REACH)

Dermal LD50 mg/kg (rat)

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 6)

Printing date 22.11.2021

Version number 11 (replaces version 10)

Trade name BITUMINOUS SEALING COATING 2 K STANDARD COMP.B

(Contd. of page 5)

Revision: 22.11.2021

· Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information		
· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accordi IMO instruments	ing to Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 7)

Page 7/7

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2021

Version number 11 (replaces version 10)

Revision: 22.11.2021

Trade name BITUMINOUS SEALING COATING 2 K STANDARD COMP.B

(Contd. of page 6)

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* * Data compared to the previous version altered.

GB ·