Printing date 23.09.2021 Version number 5 Revision: 23.09.2021

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name DURLIN MALERLACK KHX 90 GLÄNZEND WEISS
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Lacquer
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- · Signal word Warning
- · Hazard statements

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection.
P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains 2-butanone oxime, phthalic anhydride, cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

(Contd. on page 2)

Printing date 23.09.2021 Version number 5 Revision: 23.09.2021

# Trade name DURLIN MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 1)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture consisting of the following components with harmless additives.

Dangerous components:		10.050/
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy  Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	10-25%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide ❖ Carc. 2, H351	2.5-5%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39- xxxx	NAPHTA (petroleum), hydrotreated heavy & Asp. Tox. 1, H304 EUH066	2.5-5%
CAS: 96-29-7 EINECS: 202-496-6	2-butanone oxime	<0.5%
CAS: 85-44-9 EINECS: 201-607-5	phthalic anhydride  Resp. Sens. 1, H334 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	<0.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	cobalt(II) 2-ethylhexanoate  •• Acute Tox. 4, H302; Skin Sens. 1, H317	<0.5%
CAS: 22464-99-9	2-Ethylhexansäure, Zirkoniumsalz & Repr. 2, H361	<0.5%

# SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**No further relevant information available.

Printing date 23.09.2021 Version number 5 Revision: 23.09.2021

#### Trade name DURLIN MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 2)

# SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

- 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.

# SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

Not required.

Wear protective clothing.

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

# SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep breathing equipment ready.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: Store only in the original container.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class 3
- · 7.3 Specific end use(s) No further relevant information available.

**-** -

Printing date 23.09.2021 Version number 5 Revision: 23.09.2021

#### Trade name DURLIN MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 3)

## SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

# 136-52-7 cobalt(II) 2-ethylhexanoate

WEL Long-term value: 0.1 mg/m³

as Co; Carc, Sen

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

- · Hand protection Protective gloves.
- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses recommended during refilling.
- · Body protection: Protective work clothing.

# SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Smell: Characteristic

· Boiling point or initial boiling point and

boiling range 107 °C

· Lower and upper explosion limit

 · Lower:
 0.6 Vol %

 · Upper:
 7.0 Vol %

 · Flash point:
 36 °C

· Self-inflammability: Product is not selfigniting.

Decomposition temperature: Not determined.

· Viscosity:

· dynamic at 20 °C: 1500 mPas

· Solubility

· Water: Not miscible or difficult to mix

· Partition coefficient n-octanol/water (log

value) Not determined.

· Steam pressure at 20 °C: 1 hPa

(Contd. on page 5)

Printing date 23.09.2021 Version number 5 Revision: 23.09.2021

#### Trade name DURLIN MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 4)

· Density and/or relative density

· Density at 20 °C 1.3 g/cm<sup>3</sup> · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

Ignition temperature: 240 °C

· Explosive properties: Product is not explosive. However, formation of

explosive air/steam mixtures is possible.

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void

Flammable liquids Flammable liquid and vapour.

Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void

· Substances and mixtures, which emit

Void flammable gases in contact with water Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void Corrosive to metals Void · Desensitised explosives Void

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity
- · LD/LC50 values that are relevant for classification:

NAPHTA (petroleum), hydrotreated heavy

Oral LD50 >2,000 mg/kg (rat)

(Contd. on page 6)

Printing date 23.09.2021 Version number 5 Revision: 23.09.2021

#### Trade name DURLIN MALERLACK KHX 90 GLÄNZEND WEISS

Dermal	LD50	>2,000 mg/kg (rabbit) (Contd. of page 5)
96-29-7	2-buta	anone oxime
Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	1,100 mg/kg (ATE)

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

### NAPHTA (petroleum), hydrotreated heavy

IC 50 >100 mg/l (Pseudokirchneriella subcapitata (Alge))

LC50 >100 mg/l (Oncorhynchus mykiss (Regenbogenforelle))

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

# SECTION 14: Transport information - 14.1 UN number or ID number - ADR, ADN, IMDG Void - IATA UN1263 - 14.2 UN proper shipping name - ADR, ADN, IMDG Void

(Contd. on page 7)

Printing date 23.09.2021 Version number 5 Revision: 23.09.2021

#### Trade name DURLIN MALERLACK KHX 90 GLÄNZEND WEISS

		(Contd. of page
IATA	PAINT	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG		
Class	Void	
IATA		
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group		
ADR, IMDG	Void	
IATA	III	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk accordi	ng to	
IMO instruments	Not applicable.	
UN "Model Regulation":	Void	

# SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Relevant phrases

- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H350 May cause cancer.
- H351 Suspected of causing cancer.

(Contd. on page 8)

Printing date 23.09.2021 Version number 5 Revision: 23.09.2021

#### Trade name DURLIN MALERLACK KHX 90 GLÄNZEND WEISS

(Contd. of page 7)

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Contact: chemikalieninfo@murexin.com (+43 02622/27401)

## Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 1B: Carcinogenicity - Category 1B

Carc. 2: Carcinogenicity - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 1: Specific target organ toxicity (single exposure) - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* \* Data compared to the previous version altered.