

Safety data sheet according to UK REACH

Printing date 05.09.2024

Version number 6 (replaces version 5)

Revision: 05.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name** EPOXY EXPRESSHARZ EP 90 KOMP. B
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MUREXIN GmbH
Franz v. Furtenbachstr. 1
A-2700 Wiener Neustadt
Tel.: +43 (0)2622/27401
- **Informing department:** chemikalieninfo@murexin.com
- **1.4 Emergency telephone number:**
UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS05 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Benzyl alcohol
3-aminomethyl-3,5,5-trimethylcyclohexylamine
phenol, styrenated
- **Hazard statements**
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

(Contd. on page 2)

Safety data sheet according to UK REACH

Printing date 05.09.2024

Version number 6 (replaces version 5)

Revision: 05.09.2024

Trade name EPOXY EXPRESSHARZ EP 90 KOMP. B

(Contd. of page 1)

- P103 Read carefully and follow all instructions.
 P260 Do not breathe mist/vapours/spray.
 P280 Wear protective gloves / eye protection.
 P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components with harmless additives.

· Dangerous components:

CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38-xxxx	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	25-50%
CAS: 1477-55-0 EINECS: 216-032-5	m-phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	≥10-<25%
CAS: 2855-13-2 EINECS: 220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥0.001 %	10-25%
EC number: 701-443-9 Reg.nr.: 01-2119980970-27-xxxx	Phenol, mono- + distyrenated (MSP+DSP) ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Skin Sens. 1A, H317	≥5-<10%
CAS: 90-72-2 EINECS: 202-013-9	2,4,6-tris(dimethylaminomethyl)phenol ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	≥5-<10%
CAS: 102-71-6 EINECS: 203-049-8	Triethanolamine ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥5-<10%
CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17-xxxx	salicylic acid ⚠ Repr. 2, H361d ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302	≥3-≤5%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25-xxxx	3,3,5-trimethylhexamethylene-diamine ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317	1-2.5%
EC number: 700-960-7	Phenol, methylstyrenated ⚠ Skin Irrit. 2, H315; Skin Sens. 1B, H317 Aquatic Chronic 3, H412	≥1-<2.5%

GB

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 05.09.2024

Version number 6 (replaces version 5)

Revision: 05.09.2024

Trade name EPOXY EXPRESSHARZ EP 90 KOMP. B

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information**

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness bring patient into stable side position for transport.

· **After skin contact**

Instantly wash with water and soap and rinse thoroughly.

Seek medical treatment.

· **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.

· **After swallowing**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; instantly call for medical help.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents**

Use fire fighting measures that suit the environment.

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· **For safety reasons unsuitable extinguishing agents** Water with a full water jet.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

· **Protective equipment:** Put on breathing apparatus.

· **Additional information**

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Do not allow to enter the ground/soil.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable containers.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 05.09.2024

Version number 6 (replaces version 5)

Revision: 05.09.2024

Trade name EPOXY EXPRESSHARZ EP 90 KOMP. B

See Section 13 for information on disposal.

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep breathing equipment ready.

Use explosion-proof apparatus / fittings and spark-proof tools.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers:

Store only in the original container.

Provide floor trough without outlet.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: Keep container tightly sealed.

Storage class 8 A

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists that were valid during the compilation were used as basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Breathing equipment:

Breathing protection recommended.

Use breathing protection in case of insufficient ventilation.

Filter A/P2.

Hand protection Protective gloves.

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

GB

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 05.09.2024

Version number 6 (replaces version 5)

Revision: 05.09.2024

Trade name EPOXY EXPRESSHARZ EP 90 KOMP. B

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state	Fluid
· Colour:	Yellowish
· Smell:	Amine-like
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	180 °C
· Lower and upper explosion limit	
· Lower:	1.3 Vol %
· Upper:	13 Vol %
· Flash point:	130 °C
· Auto-ignition temperature:	305 °C
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	400-700 mPas
· Solubility	
· Water:	not miscible
· Partition coefficient n-octanol/water (log value)	Not determined.
· Steam pressure at 20 °C:	0.1 hPa
· Density and/or relative density	
· Density at 20 °C	1 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Solvent content:	
· Solids content:	0.0 %
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 05.09.2024

Version number 6 (replaces version 5)

Revision: 05.09.2024

Trade name EPOXY EXPRESSHARZ EP 90 KOMP. B

(Contd. of page 5)

· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Corrosive gases/vapours
Poisonous gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**
Harmful if swallowed.

- **LD/LC50 values that are relevant for classification:**

100-51-6 Benzyl alcohol

Oral	LD50	1,230 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	LD50	1,030 mg/kg (ATE)
------	------	-------------------

- **Skin corrosion/irritation**
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

69-72-7 salicylic acid

List II; III

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC 50	37 mg/l (Acartia Tonsa) (DIN 38412 (72h))
	42 mg/l (G) (DIN 38412 24h)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 05.09.2024

Version number 6 (replaces version 5)

Revision: 05.09.2024

Trade name EPOXY EXPRESSHARZ EP 90 KOMP. B


(Contd. of page 6)

- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Harmful to aquatic organisms
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Water hazard class (Germany) 2 (Self-assessment): hazardous for water.
Do not allow product to reach ground water, water bodies or sewage system.
Danger to drinking water if even small quantities leak into soil.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must be specially treated under adherence to official regulations.
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:**
Disposal must be made according to official regulations.
Non contaminated packagings can be used for recycling.
- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

SECTION 14: Transport information

- | | |
|--|--|
| <ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA | <p style="text-align: center;">UN1760</p> |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA | <p style="text-align: center;">1760 CORROSIVE LIQUID, N.O.S. (m-phenylenebis(methylamine), ISOPHORONEDIAMINE)</p> <p style="text-align: center;">CORROSIVE LIQUID, N.O.S. (m-phenylenebis(methylamine), ISOPHORONEDIAMINE)</p> |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA | <div style="text-align: center;">  <p>8</p> </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: center;">8 Corrosive substances.</p> <p style="text-align: center;">8</p> |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | <p style="text-align: center;">II</p> |

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 05.09.2024

Version number 6 (replaces version 5)

Revision: 05.09.2024

Trade name EPOXY EXPRESSHARZ EP 90 KOMP. B

(Contd. of page 7)

· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user Warning: Corrosive substances.	
· Kemler Number:	80
· EMS Number:	F-A,S-B
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk according to IMO instruments Not applicable.	
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	E
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (M-PHENYLENEBIS(METHYLAMINE), ISOPHORONEDIAMINE), 8, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361d Suspected of damaging the unborn child.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 9)

Safety data sheet according to UK REACH

Printing date 05.09.2024

Version number 6 (replaces version 5)

Revision: 05.09.2024

Trade name EPOXY EXPRESSHARZ EP 90 KOMP. B

(Contd. of page 8)

H412 Harmful to aquatic life with long lasting effects.

· **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

GB