Printing date 15.09.2021 Version number 33 Revision: 15.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name EPOXY-BASISHARZ EP 70 BM KOMP. B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



health hazard

Repr. 2 H361d Suspected of damaging the unborn child.



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS05 GHS07 GHS08 GHS09

· Signal word Danger

(Contd. on page 2)

Printing date 15.09.2021 Version number 33 Revision: 15.09.2021

Trade name EPOXY-BASISHARZ EP 70 BM KOMP. B

(Contd. of page 1)

· Hazard-determining components of labelling:

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Benzyl alcohol salicylic acid

m-phenylenebis(methylamine)

· Hazard statements

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
Suspected of damaging the unborn shild

H361d Suspected of damaging the unborn child. H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Mixture consisting of the following components with harmless additives.

Epoxidharzhärter auf Basis verschiedener Polyamine

· Dangerous components:		
CAS: 38294-64-3 NLP: 500-101-4	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	
CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38- xxxxx	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	25-50%
CAS: 1477-55-0 EINECS: 216-032-5	m-phenylenebis(methylamine) Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412	10-25%
CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17- xxxx	salicylic acid Repr. 2, H361d Eye Dam. 1, H318 Acute Tox. 4, H302	2.5-5%

Printing date 15.09.2021 Version number 33 Revision: 15.09.2021

Trade name EPOXY-BASISHARZ EP 70 BM KOMP. B

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Take affected persons into the open air and position comfortably

Seek medical treatment in case of complaints.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

If skin irritation continues, consult a doctor.

Instantly wash with water and soap and rinse thoroughly.

- After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- After swallowing

Do not induce vomiting; instantly call for medical help.

Rinse out mouth and then drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

- 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Put on breathing apparatus.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Dilute with much water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 15.09.2021 Version number 33 Revision: 15.09.2021

Trade name EPOXY-BASISHARZ EP 70 BM KOMP. B

See Section 13 for information on disposal.

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Open and handle container with care.

Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep breathing equipment ready.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- · Requirements to be met by storerooms and containers:

Provide floor trough without outlet.

Store only in the original container.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Protect from frost.

Store under dry conditions.

Keep container tightly sealed.

- · Storage class 8 A
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

Filter A/P2

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

- · Hand protection Protective gloves.
- Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of the following materials:

Leather gloves

Strong gloves

(Contd. on page 5)

Printing date 15.09.2021 Version number 33 Revision: 15.09.2021

Trade name EPOXY-BASISHARZ EP 70 BM KOMP. B

(Contd. of page 4)

- · Eye/face protection Safety glasses recommended during refilling.
- · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Smell:
Fluid
Yellowish
Amine-like

· Boiling point or initial boiling point and

boiling range 205 °C (100-51-6 Benzyl alcohol)

· Lower and upper explosion limit

 Lower:
 1.3 Vol % (100-51-6 Benzyl alcohol)

 Upper:
 13 Vol % (100-51-6 Benzyl alcohol)

· Flash point: >100 °C

· **Self-inflammability:** Product is not selfigniting.

· **Decomposition temperature:** Not determined.

· **pH at 20 °C** 8-11

Solubility

• Water: Not determined.

· Partition coefficient n-octanol/water (log

value) Not determined.

· Steam pressure at 20 °C: 0.1 hPa

· Density and/or relative density

Density at 20 °C
 Relative density
 Vapour density
 1.1 g/cm³
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

Important information on protection of health

and environment, and on safety.

• Explosive properties: Product is not explosive.

Void

Solvent content:

· Water: 0.1 % · Solids content: 0.0 %

· Change in condition

• Evaporation rate Not determined.

Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void

Self-heating substances and mixtures Substances and mixtures, which emit

flammable gases in contact with water Void
Oxidising liquids Void

(Contd. on page 6)

Printing date 15.09.2021 Version number 33 Revision: 15.09.2021

Trade name EPOXY-BASISHARZ EP 70 BM KOMP. B

		(Contd. of page 5
Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Poisonous gases/vapours

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if swallowed or if inhaled.

· LD/LC5	· LD/LC50 values that are relevant for classification:				
100-51-	6 Benz	zyl alcohol			
Oral	LD50	1,230 mg/kg (rat)			
Dermal	LD50	2,000 mg/kg (rbt)			

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- · Reproductive toxicity Suspected of damaging the unborn child.
- 11.2 Information on other hazards

· Endocrine disrupting properties		
69-72-7	salicylic acid	List II; III
128-37-0	Butylated hydroxytoluene	List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- PRT: Not applicable
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

(Contd. on page 7)

Printing date 15.09.2021 Version number 33 Revision: 15.09.2021

Trade name EPOXY-BASISHARZ EP 70 BM KOMP. B

Danger to drinking water if even small quantities leak into soil.

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Can be deposited with household garbage after solidification following consultation with the operator of the waste disposal facility and the pertinent authorities and under adherence to the necessary technical regulations.

Must be specially treated under adherence to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage

Waste disposal key number:

55903

Harzrückstände, nicht ausgehärtet gefährlich

SECTION 14: Transport information

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

14.1 UN number or ID number ADR, IMDG, IATA	UN1760
14.2 UN proper shipping name	1760 CORROSIVE LIQUID, N.O.S. (r
IMDG, IATA	phenylenebis(methylamine), Benzyl alcoho ENVIRONMENTALLY HAZARDOUS CORROSIVE LIQUID, N.O.S. (n
IIIDO, IATA	phenylenebis(methylamine), Benzyl alcohol)
14.3 Transport hazard class(es)	
ADR	
Class	8 Corrosive substances.
Label	8
IMDG, IATA	
Class	8 Corrosive substances.
Label	8
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	
Marine pollutant:	Yes
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Corrosive substances.
	(Contd. on pag

Printing date 15.09.2021 Version number 33 Revision: 15.09.2021

Trade name EPOXY-BASISHARZ EP 70 BM KOMP. B

	(Contd. of page 7
· Kemler Number:	80
· EMS Number:	F-A,S-B
· Stowage Category	В
· Stowage Code	SW2 Clear of living quarters.
· 14.7 Maritime transport in bulk accord	ing to
IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Transport category	2
· Tunnel restriction code	E
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (M PHENYLENEBIS(METHYLAMINE), BENZYI ALCOHOL), 8, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H361d Suspected of damaging the unborn child.
- H412 Harmful to aquatic life with long lasting effects.
- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 9)

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.09.2021 Version number 33 Revision: 15.09.2021

Trade name EPOXY-BASISHARZ EP 70 BM KOMP. B

(Contd. of page 8)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 2: Reproductive toxicity – Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.