```
Printing date 16.09.2021
                               Version number 4 (replaces version 3)
                                                                              Revision: 16.09.2021
   SECTION 1: Identification of the substance/mixture and of the company/undertaking
   · 1.1 Product identifier
  · Trade name EPOXY-BINDEMITTEL EP 220 KOMP. B
  · 1.2 Relevant identified uses of the substance or mixture and uses advised against
   No further relevant information available.
  · Application of the substance / the mixture Hardening agent/ Curing agent
  · 1.3 Details of the supplier of the safety data sheet
  · Manufacturer/Supplier:
   MUREXIN GmbH
   Franz v. Furtenbachstr. 1
   A-2700 Wiener Neustadt
   Tel.: +43 (0)2622/27401
  · Informing department: chemikalieninfo@murexin.com
   1.4 Emergency telephone number:
   UK National poisons Emergency number.: +44 (0) 870 600 6266
   SECTION 2: Hazards identification
  · 2.1 Classification of the substance or mixture
   Classification according to Regulation (EC) No 1272/2008
            corrosion
   Skin Corr. 1B H314 Causes severe skin burns and eye damage.
   Eye Dam. 1
                H318 Causes serious eye damage.
   Acute Tox. 4 H302 Harmful if swallowed.
   Acute Tox. 4 H312 Harmful in contact with skin.
   Acute Tox. 4 H332 Harmful if inhaled.
  · 2.2 Label elements
  · Labelling according to Regulation (EC) No 1272/2008
    The product is classified and labelled according to the CLP regulation.
   · Hazard pictograms
    GHS05 GHS07
  · Signal word Danger
  · Hazard-determining components of labelling:
   Dipropylentriamin
   Benzyl alcohol
  · Hazard statements
   H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
   H314
                      Causes severe skin burns and eye damage.
  · Precautionary statements
   P101
                     If medical advice is needed, have product container or label at hand.
   P102
                     Keep out of reach of children.
   P103
                     Read carefully and follow all instructions.
   P260
                     Do not breathe dusts or mists.
   P280
                     Wear protective gloves/protective clothing/eye protection/face protection.
                                                                                    (Contd. on page 2)
                                                                                                 GB
```

Printing date 16.09.2021

Version number 4 (replaces version 3)

Revision: 16.09.2021

Trade name EPOXY-BINDEMITTEL EP 220 KOMP. B

(Contd. of page 1)

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/container in accordance with local/regional/national/

Dispose of contents/container in accordance with local/regional/national/ international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture consisting of the following components with harmless additives.

| Dangerous components: | | |
|--|---|---------|
| CAS: 161278-35-9 | Dipropylentriamin | 50-100% |
| | Skin Corr. 1B, H314 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 | |
| CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38- | Benzyl alcohol 〈 Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319 | 25-50% |
| XXXXX | | |

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Instantly remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Instantly wash with water and soap and rinse thoroughly.

Instantly rinse with water.

• After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

• After swallowing Drink copious amounts of water and provide fresh air. Instantly call for doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

[·] 5.1 Extinguishing media

Suitable extinguishing agents

Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

• **5.2 Special hazards arising from the substance or mixture** Formation of poisonous gases during heating or in fires.

(Contd. on page 3)

GB

Printing date 16.09.2021

Version number 4 (replaces version 3)

Revision: 16.09.2021

(Contd. of page 2)

Trade name EPOXY-BINDEMITTEL EP 220 KOMP. B

5.3 Advice for firefighters

· Protective equipment:

Wear self-contained breathing apparatus.

Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures *Put on breathing apparatus.*

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter drainage system, surface or ground water. **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep breathing equipment ready.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

- · Requirements to be met by storerooms and containers: Store only in the original container.
- Information about storage in one common storage facility:
- Store away from foodstuffs.

Do not store together with acids.

· Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

- · Storage class 8 A
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists that were valid during the compilation were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals. Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments.

(Contd. on page 4)

GB

Printing date 16.09.2021

Version number 4 (replaces version 3)

Revision: 16.09.2021

Trade name EPOXY-BINDEMITTEL EP 220 KOMP. B

| | (Contd. of pag |
|--|--|
| Wash hands during breaks and at the end | |
| Do not inhale gases / fumes / aerosols. | |
| Avoid contact with the eyes and skin. | |
| Breathing equipment: | |
| | on use breathing filter apparatus. In case of intensive |
| longer exposure use breathing apparatus | that is independent of circulating air. |
| Filter A/P2. | |
| Hand protection | |
| Protective gloves. | |
| Selection of the glove material on consid | leration of the penetration times, rates of diffusion and |
| degradation | |
| Material of gloves | |
| Nitrile rubber, NBR | |
| Butyl rubber, BR | |
| Penetration time of glove material | |
| The exact break trough time has to be for | ound out by the manufacturer of the protective gloves a |
| has to be observed. | · · · |
| Eye/face protection Tightly sealed safety | y glasses. |
| Body protection: Protective work clothin | |
| | - |
| | |
| SECTION 9: Physical and chemical | l properties |
| 9.1 Information on basic physical and | chamical proportios |
| General Information | chemical properties |
| Colour: | Yellowish |
| Smell: | Amine-like |
| Lower and upper explosion limit | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| Flash point: | >100 °C |
| | Product is not selfigniting. |
| | Froduct is not semigriting. |
| Self-inflammability: | Not determined |
| pН | Not determined. |
| рН Viscosity: | |
| pH Viscosity: dynamic at 20 °C: | Not determined. 100 mPas |
| pH Viscosity: dynamic at 20 °C: Solubility | 100 mPas |
| pH Viscosity: dynamic at 20 °C: Solubility Water: | 100 mPas Partly miscible |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (lo | 100 mPas Partly miscible 29 |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic value) | 100 mPas Partly miscible Not determined. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic value) Steam pressure at 20 °C: | 100 mPas Partly miscible 29 |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic value) Steam pressure at 20 °C: Density and/or relative density | 100 mPas Partly miscible Not determined. 0.1 hPa |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density Vapour density | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density Vapour density 9.2 Other information | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density Vapour density 9.2 Other information Appearance: | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. Not determined. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density Vapour density 9.2 Other information Appearance: Form: | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. Not determined. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density Vapour density 9.2 Other information Appearance: Form: Important information on protection of | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. Not determined. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Ic value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density Vapour density 9.2 Other information Appearance: Form: Important information on protection of and environment, and on safety. | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. Not determined. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Id value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density Vapour density 9.2 Other information Appearance: Form: Important information on protection of and environment, and on safety. Ignition temperature: | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. Not determined. Not determined. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Id value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density Vapour density 9.2 Other information Appearance: Form: Important information on protection of and environment, and on safety. Ignition temperature: Explosive properties: | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. Not determined. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Id value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density Vapour density 9.2 Other information Appearance: Form: Important information on protection of and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. Not determined. Not determined. Fluid Fluid 435 °C Product is not explosive. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Id value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density Vapour density 9.2 Other information Appearance: Form: Important information on protection of and environment, and on safety. Ignition temperature: Explosive properties: Solvent content: Solids content: | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. Not determined. Not determined. |
| pH Viscosity: dynamic at 20 °C: Solubility Water: Partition coefficient n-octanol/water (Id value) Steam pressure at 20 °C: Density and/or relative density Density at 20 °C Relative density Vapour density 9.2 Other information Appearance: Form: Important information on protection of and environment, and on safety. Ignition temperature: Explosive properties: | 100 mPas Partly miscible Not determined. 0.1 hPa 1 g/cm ³ Not determined. Not determined. Not determined. |

(Contd. on page 5) _____ GB -

Printing date 16.09.2021

Version number 4 (replaces version 3)

Revision: 16.09.2021

Trade name EPOXY-BINDEMITTEL EP 220 KOMP. B

| | | (Contd. of page |
|---|------|-----------------|
| Information with regard to physical haz | ard | |
| classes | | |
| Explosives | Void | |
| Flammable gases | Void | |
| Aerosols | Void | |
| Oxidising gases | Void | |
| Gases under pressure | Void | |
| Flammable liquids | Void | |
| Flammable solids | Void | |
| Self-reactive substances and mixtures | Void | |
| Pyrophoric liquids | Void | |
| Pyrophoric solids | Void | |
| Self-heating substances and mixtures | Void | |
| Substances and mixtures, which emit | | |
| flammable gases in contact with water | Void | |
| Oxidising liquids | Void | |
| Oxidising solids | Void | |
| Organic peroxides | Void | |
| Corrosive to metals | Void | |
| Desensitised explosives | Void | |

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- [•] 10.3 Possibility of hazardous reactions

Exothermic polymerisation

Strong exothermic reaction with acids

Violent reactions with strong alkalis and oxidizing agents

- **10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Irritant gases/vapours

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity

Harmful if swallowed, in contact with skin or if inhaled.

· LD/LC50 values that are relevant for classification:

100-51-6 Benzyl alcohol

Oral LD50 1,230 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rbt)

- Skin corrosion/irritation
- Causes severe skin burns and eye damage.
- · Serious eye damage/irritation
- Causes serious eye damage.

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 6)

GB

Printing date 16.09.2021

Version number 4 (replaces version 3)

Revision: 16.09.2021

Trade name EPOXY-BINDEMITTEL EP 220 KOMP. B

(Contd. of page 5)

[.] 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: No further relevant information available.

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- [•] 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleaning agent: Water, if necessary with cleaning agent.

| <i>14.1 UN number or ID number ADR, IMDG, IATA</i> | UN2735 |
|--|---|
| 14.2 UN proper shipping name | |
| ADR | 2735 AMINES, LIQUID, CORROSIVE, N.O. (Dipropylentriamin) |
| IMDG, IATA | ÀMINÉS, LIQÚID, CORROSIVE, N.O. (Dipropylentriamin) |
| 14.3 Transport hazard class(es) | |
| ADR, IMDG, IATA | |
| | |
| Class | 8 Corrosive substances. |
| Label | 8 |

Printing date 16.09.2021

Version number 4 (replaces version 3)

Revision: 16.09.2021

Trade name EPOXY-BINDEMITTEL EP 220 KOMP. B

| | (Contd. of page | |
|--|---|--|
| 14.4 Packing group | | |
| ADR, IMDG, IĂTA | III | |
| 14.5 Environmental hazards: | | |
| Marine pollutant: | No | |
| 14.6 Special precautions for user | Warning: Corrosive substances. | |
| Kemler Number: | 80 | |
| EMS Number: | F-A,S-B | |
| Segregation groups | Alkalis | |
| Stowage Category | A | |
| Segregation Code | SG35 Stow "separated from" SGG1-acids | |
| 14.7 Maritime transport in bulk accord | ing to | |
| IMO instruments | Not applicable. | |
| Transport/Additional information: | | |
| ADR | | |
| Limited quantities (LQ) | 5L | |
| Transport category | 3 | |
| Tunnel restriction code | E | |
| UN "Model Regulation": | UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S (DIPROPYLENTRIAMIN), 8, III | |

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled.
- **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)

Abbreviations and acronyms:
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent

GB

Printing date 16.09.2021

Version number 4 (replaces version 3)

Revision: 16.09.2021

Trade name EPOXY-BINDEMITTEL EP 220 KOMP. B

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

** Data compared to the previous version altered.

(Contd. of page 7)

GB —