Printing date 13.08.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### · 1.1 Product identifier

- Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. A
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Spacings sealent
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: MUREXIN GmbH Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401
- · Informing department: chemikalieninfo@murexin.com
- 1.4 Emergency telephone number:
- UK National poisons Emergency number.: +44 (0) 870 600 6266

## SECTION 2: Hazards identification

2.1 Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

health hazard

Repr. 1B

H360F May damage fertility.



Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### · 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



## · Signal word Danger

• Hazard-determining components of labelling: Bisphenol A epoxy resin oxirane, mono[(C12-14-alkyloxy)methyl] derivs Bisphenol F diglycidyl ether, mixture of isomers Bisphenol-F-epichlorohydrin resin 1,6-bis(2,3-epoxypropoxy)hexane • Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H360F May damage fertility.

H412 Harmful to aquatic life with long lasting effects.

GB

Printing date 13.08.2024

Version number 9 (replaces version 8)

Revision: 13.08.2024

## Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. A

	(Contd. of page 1)
• Precautionary	statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.
· Additional info	ormation:
Restricted to p	rofessional users.
Contains epoxy	/ constituents. May produce an allergic reaction.
· 2.3 Other haza	
· Results of PB	T and vPvB assessment
· PBT: Not appli	cable

• **vPvB:** Not applicable.

# SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture consisting of the following components with harmless additives.

CAS: 1675-54-3	Bisphenol A epoxy resin	≥10-<25%
EINECS: 216-823-5	<ul> <li>Aquatic Chronic 2, H411</li> <li>Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317</li> <li>EUH205</li> <li>Specific concentration limits: Eye Irrit. 2; H319: C ≥5 % Skin Irrit. 2; H315: C ≥ 5 %</li> </ul>	
CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural substance with a Community workplace exposure limit	5-10%
CAS: 12001-26-2	Mica substance with a Community workplace exposure limit	5-10%
CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38- xxxxx	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	2.5-5%
CAS: 68609-97-2 EINECS: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs Repr. 1B, H360F Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-5%
EC number: 701-263-0 Reg.nr.: 01-2119454392-40- 0003	Bisphenol F diglycidyl ether, mixture of isomers Consisting of: 9003-36-5 Bisphenol-F- epichlorohydrin resin Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1A, H317	2.5-5%
ELINCS: 432-430-3 Reg.nr.: 01-0000017860-69-xxx	Polyamidwachs Aquatic Chronic 4, H413	2.5-5%

Printing date 13.08.2024

Version number 9 (replaces version 8)

Revision: 13.08.2024

## Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. A

	1	(Contd. of page 2)
CAS: 9003-36-5	Bisphenol-F-epichlorohydrin resin	<i>≥</i> 0.1-<0.25%
NLP: 500-006-8	Aquatic Chronic 2, H411	
Reg.nr.: 01-2119454392-40-	Skin Irrit. 2, H315; Skin Sens. 1, H317	
0001	ĚUH205	
CAS: 933999-84-9	1,6-bis(2,3-epoxypropoxy)hexane	<i>≥</i> 0.1-<0.5%
EC number: 618-939-5	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens.	
Reg.nr.: 01-2119463471-41	1, H317	
-	Aquatic Chronic 3, H412	

## SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information Instantly remove any clothing soiled by the product.

- After inhalation Supply fresh air and call for doctor for safety reasons.
- · After skin contact

Instantly wash with water and soap and rinse thoroughly.

- If skin irritation continues, consult a doctor.
- After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents

Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- · 6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Keep dirty washing water for appropriate disposal.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation.

- <sup>•</sup> 6.4 Reference to other sections
- See Section 7 for information on safe handling
- See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

(Contd. on page 4)

*Printing date 13.08.2024* 

#### Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. A

(Contd. of page 3)

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep containers tightly sealed. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers: Store only in the original container.
- Information about storage in one common storage facility: Store away from foodstuffs.

Do not store together with oxidising and acidic materials as well as heavy-metal compounds.

• Further information about storage conditions: Keep container tightly sealed.

· Storage class 6.1 C

• 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

#### 7727-43-7 barium sulphate, natural

WEL Long-term value: 10\* 4\*\* mg/m<sup>3</sup>

\*inhalable dust \*\*respirable dust

## 12001-26-2 Mica

WEL Long-term value: 10\* 0.8\*\* mg/m<sup>3</sup> \*total inhalable \*\*respirable

• Additional information: The lists that were valid during the compilation were used as basis.

#### · 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

General protective and hygienic measures

- The usual precautionary measures should be adhered to in handling the chemicals.
- Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Breathing protection recommended.
- · Hand protection Protective gloves.
- Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Tightly sealed safety glasses.

· Body protection: Protective work clothing.

(Contd. on page 5)

GB

Printing date 13.08.2024

## Version number 9 (replaces version 8)

Revision: 13.08.2024

## Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. A

(Contd. of page 4)

SECTION 9: Physical and chemical pro	operties	
• 9.1 Information on basic physical and cher	mical properties	
· General Information		
· Physical state	Fluid	
· Colour:	White	
· Smell:	Characteristic	
• Boiling point or initial boiling point and		
boiling range	>100 °C	
Flash point:	>100 °C	
рН	Not determined.	
Solubility		
Water:	not miscible	
• Steam pressure at 23 °C:	>0 hPa	
· Density and/or relative density		
· Density at 20 °C	1.4 g/cm³	
-		-
9.2 Other information		
· Appearance:	Deatr	
· Form:	Pasty	
Important information on protection of hea		
and environment, and on safety.	Draduct is not colficiation	
Self-inflammability:	Product is not selfigniting.	
· Explosive properties:	Product is not explosive.	
<ul> <li>Information with regard to physical haza</li> </ul>	ard	
classes		
<sup>.</sup> Explosives	Void	
<sup>.</sup> Flammable gases	Void	
· Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
<sup>.</sup> Flammable liquids	Void	
· Flammable solids	Void	
<ul> <li>Self-reactive substances and mixtures</li> </ul>	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
<ul> <li>Substances and mixtures, which emit</li> </ul>		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
<ul> <li>Desensitised explosives</li> </ul>	Void	

## SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: None

(Contd. on page 6)

GB

Printing date 13.08.2024

## Version number 9 (replaces version 8)

Revision: 13.08.2024

# Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. A

(Contd. of page 5)

		: Toxicological information
		<b>on on hazard classes as defined in Regulation (EC) No 1272/2008</b> Based on available data, the classification criteria are not met.
	-	es that are relevant for classification:
1675-54	-3 Bis	phenol A epoxy resin
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
100-51-	6 Benz	yl alcohol
Oral	LD50	1,230 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Polyam	idwac	hs
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
9003-36	-5 Bis	phenol-F-epichlorohydrin resin
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
		n/irritation
Causes		
		amage/irritation s eye irritation.
		tagenicity Based on available data, the classification criteria are not met.
		ty Based on available data, the classification criteria are not met.
Reprod	uctive	toxicity
May dar		
		exposure Based on available data, the classification criteria are not met. In exposure Based on available data, the classification criteria are not met.
		zard Based on available data, the classification criteria are not met.
		cicological information:
CMR ef	fects (	carcinogenity, mutagenicity and toxicity for reproduction) - on on other hazards
Endocr	ine dis	rupting properties
	the inc	gredients is listed.

# SECTION 12: Ecological information

· 12.1 Toxicity				
· Aquatic toxicity:				
Polyamidwachs				
EC 50	EC 50 >1,000 mg/l (G) (24h/48h)			
LC50	>1,000 mg/l (Oncorhynchus mykiss (Regenbogenforelle))			
	134 mg/l (G) (48hr; EPIWIN software)			
9003-36-5 Bisphenol-F-epichlorohydrin resin				
EC 50	EC 50 1.8 mg/l (Desmodesmus subspicatus)			
	1.6 mg/l (G)			
IC 50	>100 mg/l (bacteria)			
LC50	0.55 mg/l (Lepomis macrochirus (Fisch))			
<ul> <li>12.2 Persistence and degradability No further relevant information available.</li> <li>12.3 Bioaccumulative potential No further relevant information available.</li> <li>12.4 Mobility in soil No further relevant information available.</li> </ul>				

(Contd. on page 7)

Printing date 13.08.2024

Version number 9 (replaces version 8)

## Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. A

(Contd. of page 6)

- <sup>•</sup> 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:
- Harmful to aquatic organisms

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

## SECTION 13: Disposal considerations

## <sup>·</sup> 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
<ul> <li>14.1 UN number or ID number</li> <li>ADR, ADN, IMDG, IATA</li> </ul>	Void
<ul> <li>14.2 UN proper shipping name</li> <li>ADR, ADN, IMDG, IATA</li> </ul>	Void
<ul> <li>14.3 Transport hazard class(es)</li> </ul>	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
<ul> <li>14.7 Maritime transport in bulk accordin IMO instruments</li> </ul>	n <b>g to</b> Not applicable.
· UN "Model Regulation":	Void

## SECTION 15: Regulatory information

<sup>•</sup> 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

## · Regulated explosives precursors

None of the ingredients is listed.

(Contd. on page 8)

<sup>-</sup> GB

Printing date 13.08.2024

Revision: 13.08.2024

#### Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. A

(Contd. of page 7)

GB

## · Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

#### · Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

#### **Contact:** chemikalieninfo@murexin.com (+43 02622/27401)

Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Repr. 1B: Reproductive toxicity – Category 1B Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

\* \* Data compared to the previous version altered.