Printing date 13.08.2024 Version number 11 (replaces version 10) Revision: 13.08.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Sens. 1

H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS05 GHS07 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Reaction product of Fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing date 13.08.2024 Version number 11 (replaces version 10) Revision: 13.08.2024

### Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. B

(Contd. of page 1)

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P260 Do not breathe dusts or mists.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- **Description:** Mixture consisting of the following components with harmless additives.

· Dangerous components:		
EC number: 701-046-0 Reg.nr.: 01-2119972321-42- xxxx	Reaction product of Fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction  Eye Dam. 1, H318 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1A, H317	50-100%
CAS: 2855-13-2 EINECS: 220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine  Skin Corr. 1B, H314; Eye Dam. 1, H318  Acute Tox. 4, H302; Skin Sens. 1A, H317  ATE: LD50 oral: 1,030 mg/kg  Specific concentration limit:  Skin Sens. 1A; H317: C ≥0.001 %	25-50%

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information

Take affected persons into the open air.

Instantly remove any clothing soiled by the product.

· After inhalation

In case of unconsciousness bring patient into stable side position for transport.

Supply fresh air; consult doctor in case of symptoms.

After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing Seek immediate medical advice.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB

Printing date 13.08.2024 Version number 11 (replaces version 10)

Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. B

(Contd. of page 2)

Revision: 13.08.2024

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

Use fire fighting measures that suit the environment.

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- · 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Dilute with much water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: Keep breathing equipment ready.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: Store only in the original container.
- · Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with oxidising and acidic materials as well as heavy-metal compounds.

· Further information about storage conditions:

Protect from frost.

Keep container tightly sealed.

- · Storage class 8 A
- · 7.3 Specific end use(s) No further relevant information available.

CD.

Printing date 13.08.2024 Version number 11 (replaces version 10) Revision: 13.08.2024

Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. B

(Contd. of page 3)

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Not necessary if room is well-ventilated.

Use breathing protection in case of insufficient ventilation.

Filter A/P2.

- · Hand protection Protective gloves.
- Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Tightly sealed safety glasses.
- · Body protection: Protective work clothing.

## SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Smell:
Melting point/freezing point:

Fluid

Yellowish

Amine-like

Not determined

· Boiling point or initial boiling point and

boiling range >200 °C

· Lower and upper explosion limit

Lower: Not determined.
Upper: 1.2 Vol %
Flash point: >100 °C
Auto-ignition temperature: 300 °C
pH at 20 °C
pH at 20 °C

· Viscosity:

Kinematic viscositydynamic at 20 °C:Not determined.148 mPas

Solubility

· Water: Unsoluble · Steam pressure: Not determined.

Density and/or relative density

· Density at 20 °C 0.9 g/cm³

(Contd. on page 5)

Printing date 13.08.2024 Version number 11 (replaces version 10) Revision: 13.08.2024

#### Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. B

(Contd. of page 4)

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.
 Explosive properties: Product is not explosive.

· Solvent content:

· Solids content: 0.0 %

· Information with regard to physical hazard classes

· Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

· Corrosive to metals

· Desensitised explosives

· Conditions to be avoided: No decomposition if used according to specifications.

Void

Void

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Poisonous gases/vapours

Corrosive gases/vapours

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

$\cdot LD/L$	C50 values	that are	relevant :	for clas	sification

Oral LD50 >5,000 mg/kg (rat)
Dermal LD50 >2,000 mg/kg (rabbit)

## 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral LD50 1,030 mg/kg (ATE)

(Contd. on page 6)

Printing date 13.08.2024 Version number 11 (replaces version 10) Revision: 13.08.2024

#### Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. B

(Contd. of page 5)

· Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity:

EC 50 3.3 mg/l (G) (48h)

### 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC 50 37 mg/l (Acartia Tonsa) (DIN 38412 (72h))

42 mg/l (G) (DIN 38412 24h)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

The declaration of the ecology refers to the active agent.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Can be deposited with household garbage after solidification following consultation with the operator of the waste disposal facility and the pertinent authorities and under adherence to the necessary technical regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 13.08.2024 Version number 11 (replaces version 10) Revision: 13.08.2024

## Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. B

(Contd. of page 6)

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleaning agent: Water, if necessary with cleaning agent.

14.1 UN number or ID number ADR, IMDG, IATA	UN2735
14.2 UN proper shipping name ADR	2735 AMINES, LIQUID, CORROSIVE, N.O.S (ISOPHORONEDIAMINE), ENVIRONMENTALL HAZARDOUS
IMDG IATA	AMINES, LIQUID, CORROSIVE, N.O.S (ISOPHORONEDIAMINE), MARINE POLLUTANT AMINES, LIQUID, CORROSIVE, N.O.S
	(ISOPHORONEDIAMINE)
14.3 Transport hazard class(es)	
ADR, IMDG	
Class Label	8 Corrosive substances. 8
Sign of the sign o	9. Compains out atomass
Class Label	8 Corrosive substances. 8
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances: Reaction product of Fatty acids, Calkyl with amines, polyethylenepoly tetraethylenepentamine fraction
Marine pollutant: Special marking (ADR):	Yes Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Corrosive substances.
Kemler Number: EMS Number:	80 F-A,S-B
Segregation groups	(SGG18) Alkalis A
Stowage Category Segregation Code	SG35 Stow "separated from" SGG1-acids

(Contd. on page 8)

Printing date 13.08.2024 Version number 11 (replaces version 10) Revision: 13.08.2024

#### Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. B

(Contd. of page 7)

Transport/Additional information:

ADR

Limited quantities (LQ)
Transport category
Tunnel restriction code

UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S.
(ISOPHORONEDIAMINE), 8, III,
ENVIRONMENTALLY HAZARDOUS

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)

Printing date 13.08.2024 Version number 11 (replaces version 10) Revision: 13.08.2024

### Trade name EPOXYKLEBEMÖRTEL WEISS EKY 91 KOMP. B

(Contd. of page 8)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* Data compared to the previous version altered.