Revision: 04.11.2021

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2021

Version number 6 (replaces version 5)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name OBJEKTGRUNDIERUNG OG 80 KOMP.A
- · Article number: 31204/6
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Coating
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07 GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

oxirane, mono[(C12-14-alkyloxy)methyl] derivs

1,4-bis(2,3-epoxypropoxy)butane

bis[4-(2,3-epoxypropoxy)phenyl]propane

formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol 1,6-bis(2,3-epoxypropoxy)hexane

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 04.11.2021 Version number 6 (replaces version 5) Revision: 04.11.2021

### Trade name OBJEKTGRUNDIERUNG OG 80 KOMP.A

(Contd. of page 1)

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P261 Avoid breathing mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Contains epoxy constituents. May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Mixture consisting of the following components with harmless additives.

Dangerous components:		
CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26- 0XXX	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)  Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317  EUH205  Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	10-25%
CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural substance with a Community workplace exposure limit	10-25%
CAS: 100-51-6 EINECS: 202-859-9 Reg.nr.: 01-2119492630-38- xxxxx	Benzyl alcohol  Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	2.5-5%
CAS: 68609-97-2 EINECS: 271-846-8	oxirane, mono[(C12-14-alkyloxy)methyl] derivs  •• Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-5%
CAS: 2425-79-8 EINECS: 219-371-7 Reg.nr.: 01-2119494060-45	1,4-bis(2,3-epoxypropoxy)butane  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	1-2.5%
CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydrotreated light  Flam. Liq. 3, H226  Asp. Tox. 1, H304	1-2.5%
CAS: 1675-54-3 EINECS: 216-823-5	bis[4-(2,3-epoxypropoxy)phenyl]propane  Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	1-2.5%

Printing date 04.11.2021 Version number 6 (replaces version 5) Revision: 04.11.2021

#### Trade name OBJEKTGRUNDIERUNG OG 80 KOMP.A

		d. of page 2)
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40- 0001	formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317 EUH205	0.5-1%
CAS: 933999-84-9 EC number: 618-939-5 Reg.nr.: 01-2119463471-41	1,6-bis(2,3-epoxypropoxy)hexane  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317  Aquatic Chronic 3, H412	0.5-1%

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

Supply fresh air; consult doctor in case of symptoms.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

· After swallowing

In case of persistent symptoms consult doctor.

Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

Do not allow to enter the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 04.11.2021

Version number 6 (replaces version 5)

#### Trade name OBJEKTGRUNDIERUNG OG 80 KOMP.A

(Contd. of page 3)

Revision: 04.11.2021

See Section 13 for information on disposal.

### SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and containers: Store only in the original container.
- · Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Components with critical values that require monitoring at the workplace:

### 7727-43-7 barium sulphate, natural

WEL Long-term value: 10\* 4\*\* mg/m³
\*inhalable dust \*\*respirable dust

- Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the skin.

Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air. Filter A/P2.

- · Hand protection Protective gloves.
- · Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses
- Body protection: Protective work clothing.

GE

Printing date 04.11.2021 Version number 6 (replaces version 5) Revision: 04.11.2021

#### Trade name OBJEKTGRUNDIERUNG OG 80 KOMP.A

(Contd. of page 4)

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Different according to colour · Colour:

· Smell: Characteristic

· Lower and upper explosion limit

Not determined. · Lower: · Upper: Not determined. · Flash point: Not applicable

Self-inflammability: Product is not selfigniting.

Not determined. · pH

· Viscosity:

· dynamic at 20 °C: 7,000-11,000 mPas

· Solubility

immiscible · Water:

· Partition coefficient n-octanol/water (log

Not determined. value)

13.5 hPa (Quartz (SiO2)) · Steam pressure at 1732 °C:

Density and/or relative density

1.8 g/cm<sup>3</sup> Density at 20 °C Not determined. Relative density · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health

and environment, and on safety.

Explosive properties: Product is not explosive.

Solvent content:

· Solids content: 0.0 %

· Change in condition

Not determined. · Evaporation rate

### · Information with regard to physical hazard classes

0.40000	
· Explosives	Void
Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
· Organic peroxides	Void
Corrosive to metals	Void
· Desensitised explosives	Void

Printing date 04.11.2021

Version number 6 (replaces version 5)

#### Trade name OBJEKTGRUNDIERUNG OG 80 KOMP.A

(Contd. of page 5)

Revision: 04.11.2021

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC5	0 valu	es that are relevant for classification:
25068-3		action product: bisphenol-A-(epichlorhydrin) epoxy resin (number average olecular weight = 700)
Oral	LD50	19,800 mg/kg (rabbit)
		11,400 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
100-51-	6 Benz	zyl alcohol
Oral	LD50	1,230 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)
2425-79	-8 1,4-	bis(2,3-epoxypropoxy)butane
Oral	LD50	2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
1675-54	-3 bis	[4-(2,3-epoxypropoxy)phenyl]propane
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
9003-36	-5 fori	maldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and
	phe	enol
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)

- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) -
- · 11.2 Information on other hazards

· Endocrine disrupting properties	
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane	List II
128-37-0 Butylated hydroxytoluene	List II
Decamethylcyclopentasiloxan	List II

Printing date 04.11.2021 Version number 6 (replaces version 5) Revision: 04.11.2021

#### Trade name OBJEKTGRUNDIERUNG OG 80 KOMP.A

		(Contd. of page 6)
556-67-2	octamethylcyclotetrasiloxane	List II; III
540-97-6	Dodecamethylcyclohexasiloxan	List II

### **SECTION 12: Ecological information**

· 12.1 Toxicity

12.11	said the sai
· Aquati	ic toxicity:
25068-	-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
EC 50	11 mg/l (Desmodesmus subspicatus (Alge))
	1.8 mg/l (Daphnia magna (Großer Wasserfloh))
IC 50	100 mg/l (bacteria)
LC50	2 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (semistatisch, 96h)
9003-3	6-5 formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
EC 50	1.8 mg/l (Desmodesmus subspicatus (Alge))
	1.6 mg/l (Daphnia magna (Großer Wasserfloh))
IC 50	>100 mg/l (bacteria)
LC50	0.55 mg/l (Lepomis macrochirus (Fisch))

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class (Germany) 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### **SECTION 14: Transport information**

- · 14.1 UN number or ID number
- · **ADR, IMDG, IATA** UN3082

(Contd. on page 8)

Revision: 04.11.2021

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2021

Version number 6 (replaces version 5)

### Trade name OBJEKTGRUNDIERUNG OG 80 KOMP.A

	(Contd. of page
14.2 UN proper shipping name	
ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-A-(epichlorhydrin) epoxy resin (numbe average molecular weight = 700))
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number averago molecular weight = 700), bis[4-(2,3-epoxypropoxy
IATA	phenyl]propane), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecular weight = 700))
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
<b>1 1 1 1 1 1 1 1 1 1</b>	
Class	9 Miscellaneous dangerous substances and articles.
Label	9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances: reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecular weight = 700)
Marine pollutant:	No Symbol (fish and troo)
Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Kemler Number:	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk according IMO instruments	ng to Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category Tunnel restriction code	3 (-)

(Contd. on page 9)

Printing date 04.11.2021 Version number 6 (replaces version 5) Revision: 04.11.2021

#### Trade name OBJEKTGRUNDIERUNG OG 80 KOMP.A

(Contd. of page 8)

· UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT = 700)), 9, III

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH205 Contains epoxy constituents. May produce an allergic reaction.
- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

(Contd. on page 10)

Page 10/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.11.2021

Version number 6 (replaces version 5)

### Trade name OBJEKTGRUNDIERUNG OG 80 KOMP.A

(Contd. of page 9)

Revision: 04.11.2021

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard — Category 3

\* Data compared to the previous version altered.

00