Revision: 11.05.2023

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.05.2023

Version number 5 (replaces version 4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name POLYURETHANVERSIEGELUNG PU 40 KOMP. B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Hexamethylene diisocyanate oligomers, isocyanurate poly(oxy-1,2-ethanediyl), α-tridecyl-ω-hydroxy-, phosphate Isophorone diisocyanate oligomers cyclohexyldimethylamine

Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

(Contd. on page 2)

Printing date 11.05.2023 Version number 5 (replaces version 4) Revision: 11.05.2023

Trade name POLYURETHANVERSIEGELUNG PU 40 KOMP. B

(Contd. of page 1)

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.
P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Mixture consisting of the following components with harmless additives. Aliphatisches Polyisocyanat

· Dangerous components:		
EC number: 931-274-8 Reg.nr.: 01-2119485796-17-	Hexamethylene diisocyanate oligomers, isocyanurate	25-50%
0002	Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	
EC number: 931-312-3	Isophorone diisocyanate oligomers	10-25%
Reg.nr.: 01-2119488734-24	♦ Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 9046-01-9 EC number: 618-558-4	poly(oxy-1,2-ethanediyl), α-tridecyl-ω-hydroxy-, phosphate	≥5-<10%
	Eye Dam. 1, H318 Skin Irrit. 2, H315 Aquatic Chronic 3, H412	
CAS: 98-94-2	cyclohexyldimethylamine	≥0.5-<1%
EINECS: 202-715-5 Reg.nr.: 01-2119533030-60	 ♠ Flam. Liq. 3, H226 ♠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331 ♠ Skin Corr. 1B, H314 	
	Aquatic Chronic 2, H411	
	(Contd. on page 3

Printing date 11.05.2023 Version number 5 (replaces version 4) Revision: 11.05.2023

Trade name POLYURETHANVERSIEGELUNG PU 40 KOMP. B

		(Contd. of page 2)
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37- 0001	hexamethylene diisocyanate Acute Tox. 1, H330 Resp. Sens. 1, H334 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 EUH204 Specific concentration limits: Resp. Sens. 1; H334:C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.1-<0.5%
CAS: 4098-71-9 EINECS: 223-861-6 Reg.nr.: 01-2119490408-31- 0001	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 1, H330 Resp. Sens. 1, H334 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 EUH204 Specific concentration limits: Resp. Sens. 1; H334:C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.1-<0.25%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.
- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.

(Contd. on page 4)

Printing date 11.05.2023 Version number 5 (replaces version 4) Revision: 11.05.2023

Trade name POLYURETHANVERSIEGELUNG PU 40 KOMP. B

(Contd. of page 3)

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Dilute with much water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and containers: Store only in the original container.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

822-06-0 hexamethylene diisocyanate

WEL Short-term value: 0.07 mg/m3

Long-term value: 0.02 mg/m3

Sen; as -NCO

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

WEL | Short-term value: 0.07 mg/m³

Long-term value: 0.02 mg/m³

Sen; as -NCO

· Ingredients with biological limit values:

822-06-0 hexamethylene diisocyanate

BMGV 1 umol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

· Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 5)

Printing date 11.05.2023 Version number 5 (replaces version 4) Revision: 11.05.2023

Trade name POLYURETHANVERSIEGELUNG PU 40 KOMP. B

(Contd. of page 4)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Breathing protection recommended.

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses
- Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Smell:
Odour threshold:
Melting point/freezing point:

Fluid

Colourless
Characteristic
Not determined

Not determined

Boiling point or initial boiling point and

boiling range Not determined
Flammability Not applicable.

· Lower and upper explosion limit

· Lower: Not determined.
· Upper: Not determined.
· Flash point: 76 °C

· Flash point: 76 °C · Auto-ignition temperature: 445 °C

· **Decomposition temperature:** Not determined.

· **pH** Mixture is non-soluble (in water).

· Viscosity:

• Kinematic viscosity Not determined. • dynamic at 20 °C: 200 mPas

Solubility

· Water: Partly soluble

· Partition coefficient n-octanol/water (log

value) Not determined.

Steam pressure at 20 °C: >0 hPa

(Contd. on page 6)

Printing date 11.05.2023 Version number 5 (replaces version 4) Revision: 11.05.2023

Trade name POLYURETHANVERSIEGELUNG PU 40 KOMP. B

(Contd. of page 5)

Density at 20 °C
 Relative density
 Vapour density
 1.1 g/cm³
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Liquid

Important information on protection of health

and environment, and on safety.

Self-inflammability: Product is not selfigniting.
 Explosive properties: Product is not explosive.

· Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void Substances and mixtures, which emit Void flammable gases in contact with water Oxidising liquids Void Oxidising solids Void · Organic peroxides Void Corrosive to metals Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Desensitised explosives

- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with alcohols, amines, aqueous acids and alkalis

Void

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.

· I D/I C50 va	alues that are	relevant for	classification:

98-94-2 cyclohexyldimethylamine

Oral LD50 348 mg/kg (rat)
Inhalative LC50/4 h 1.88 mg/l (rat)

Skin corrosion/irritation Causes skin irritation.

(Contd. on page 7)

Printing date 11.05.2023

Version number 5 (replaces version 4)

Trade name POLYURETHANVERSIEGELUNG PU 40 KOMP. B

(Contd. of page 6)

Revision: 11.05.2023

- · Serious eye damage/irritation Causes serious eye damage.
- · STOT-single exposure May cause respiratory irritation.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Water hazard class (Germany) 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleaning agent: Water, if necessary with cleaning agent.

· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void	
ADN, ADN, INIDG, IATA		
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
· Marine pollutant:	No	

(Contd. on page 8)

Printing date 11.05.2023 Version number 5 (replaces version 4) Revision: 11.05.2023

Trade name POLYURETHANVERSIEGELUNG PU 40 KOMP. B

		(Contd. of page 7)
14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk accord IMO instruments	ing to Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH204 Contains isocyanates. May produce an allergic reaction.

- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 1: Acute toxicity – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

(Contd. on page 9)

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.05.2023

Version number 5 (replaces version 4)

Trade name POLYURETHANVERSIEGELUNG PU 40 KOMP. B

(Contd. of page 8)

Revision: 11.05.2023

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* * Data compared to the previous version altered.

GB