Printing date 11.05.2021 Version number 15 Revision: 11.05.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name SILOLACK SL 100
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Bitumen coating
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MUREXIN GmbH

Franz v. Furtenbachstr. 1 A-2700 Wiener Neustadt Tel.: +43 (0)2622/27401

- · Informing department: chemikalieninfo@murexin.com
- · 1.4 Emergency telephone number:

UK National poisons Emergency number.: +44 (0) 870 600 6266

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3

H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02 GHS07 GHS08 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Kohlenwasserstoffe (C9-C12, n-Alkane, Isoalkane, Cycloalkane, Aromaten (2-25%))

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

Printing date 11.05.2021 Version number 15 Revision: 11.05.2021

Trade name SILOLACK SL 100

(Contd. of page 1)

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P243 Take action to prevent static discharges.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains N-[3-(dimethylamino)propyl)]-C18-ungesättigte Alkylamide. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture consisting of the following components with harmless additives.

· Dangerous components:			
EC number: 919-446-0 Reg.nr.: 2119458049-33-xxxx	Kohlenwasserstoffe (C9-C12, n-Alkane,Isoalkane, Cycloalkane, Aromaten (2-25%)) Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336 EUH066	25-50%	
CAS: 1379524-06-7 EC number: 800-353-8	N-[3-(dimethylamino)propyl)]-C18-ungesättigte Alkylamide	0.5-1%	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- · After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

- · After swallowing Do not induce vomiting; instantly call for medical help.
- **4.2 Most important symptoms and effects, both acute and delayed**No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

Printing date 11.05.2021 Version number 15 Revision: 11.05.2021

Trade name SILOLACK SL 100

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

 \cdot 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Keep containers tightly sealed.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage
- Requirements to be met by storerooms and containers: Store only in the original container.
- Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.

(Contd. on page 4)

Printing date 11.05.2021 Version number 15 Revision: 11.05.2021

Trade name SILOLACK SL 100

(Contd. of page 3)

· Individual protection measures, such as personal protective equipment

General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Filter A/P2.

· Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Tightly sealed safety glasses.

Face protection

· Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Colour: Black
· Smell: Benzen-like
· Melting point/freezing point: Not determined

· Boiling point or initial boiling point and

boiling range Not determined

· Lower and upper explosion limit

· Lower: 0.6 Vol %
 · Upper: 7 Vol %
 · Flash point: 38 °C

· **Self-inflammability:** Product is not selfigniting.

· **pH at 20 °C** n.a.

· Viscosity:

· Kinematic viscosity
· dynamic:

Not determined.

Not determined.

· Solubility

• Water: immiscible • Steam pressure at 20 °C: 40 hPa

Density and/or relative density

Density at 20 °C 0.9 g/cm³

9.2 Other information

· Appearance:

· Form: Fluid

(Contd. on page 5)

Printing date 11.05.2021 Version number 15 Revision: 11.05.2021

Trade name SILOLACK SL 100

(Contd. of page 4)

· Important information	on protection of health
	£ 4

and environment, and on safety.

Ignition temperature: >350 °C

Explosive properties: Product is not explosive. However, formation of

explosive air/steam mixtures is possible.

· Solvent separation test <3

· Solvent content:

· Solids content: 50.3 %

Information with regard to physical hazard

Explosives
 Flammable gases
 Aerosols
 Oxidising gases
 Gases under pressure

Void
Void

Flammable liquids

Flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which emit flammable gases in contact with water
Oxidising liquids
Oxidising solids

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void
Void
Void
Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

Kohlenwasserstoffe (C9-C12, n-Alkane, Isoalkane, Cycloalkane, Aromaten (2-25%))

Oral | LD50 | >15,000 mg/kg (rat) Dermal | LD50 | >3,400 mg/kg (rat)

1379524-06-7 N-[3-(dimethylamino)propyl)]-C18-ungesättigte Alkylamide

Oral | LD50 | >2,000 mg/kg (rat)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 11.05.2021 Version number 15 Revision: 11.05.2021

Trade name SILOLACK SL 100

(Contd. of page 5)

- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic to	oxicity:
Kohlenwa	rsserstoffe (C9-C12, n-Alkane,Isoalkane, Cycloalkane, Aromaten (2-25%))
EL50	4.6-10 mg/l (Pseudokirchneriella subcapitata (Alge))
	10-22 mg/l (Daphnia magna (Großer Wasserfloh))
LL50	10-30 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
1379524-0	6-7 N-[3-(dimethylamino)propyl)]-C18-ungesättigte Alkylamide
EC 50/48h	0.28 mg/l (Daphnia magna (Großer Wasserfloh))
EC 50	>0.96 mg/l (Pseudokirchneriella subcapitata (Alge))
LC50	0.94 mg/l (Brachydanio rerio (Zebrabärbling))

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water danger class (Germany) 3 (Self-assessment): extremely hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into soil.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 11.05.2021 Version number 15 Revision: 11.05.2021

Trade name SILOLACK SL 100

(Contd. of page 6)

- · Uncleaned packagings: · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name ADR	1993 FLAMMABLE LIQUID, N.O.S. (TURPENTIN SUBSTITUTE), ENVIRONMENTALL HAZARDOUS
IMDG	FLAMMABLE LIQUID, N.O.S. (TURPENTIN SUBSTITUTE, N-[3-(dimethylamino)propyl)]-C1 ungesättigte Alkylamide), MARINE POLLUTANT
IATA	FLAMMABLE LIQUID, N.O.S. (TURPENTIN SUBSTITUTE)
14.3 Transport hazard class(es)	
ADR, IMDG	
Class Label	3 Flammable liquids. 3
IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardoù substances: Kohlenwasserstoffe (C9-C12, Alkane,Isoalkane, Cycloalkane, Aromaten (2-25%,
Marine pollutant:	Yes
Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Kemler Number:	30
EMS Number: Segregation groups	F-E, <u>S-E</u> Alkalis
Stowage Category	A
14.7 Maritime transport in bulk accordi	ing to Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ) Transport category	5L
	3

Printing date 11.05.2021 Version number 15 Revision: 11.05.2021

Trade name SILOLACK SL 100

	(Contd. of page 7)	
· Tunnel restriction code	D/E	
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE), 3, III, ENVIRONMENTALLY HAZARDOUS	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H226 Flammable liquid and vapour.
- H290 May be corrosive to metals.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Contact: chemikalieninfo@murexin.com (+43 02622/27401)
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Met. Corr.1: Corrosive to metals – Category 1

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 9)

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.05.2021 Version number 15 Revision: 11.05.2021

Trade name SILOLACK SL 100

(Contd. of page 8)

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* * Data compared to the previous version altered.