

## GULLY SEAL



- > for any gully or drain
- > water-impermeable
- > fleece-laminated on both sides
- > edge zone perforation

### Product description

Fleece laminated on both sides and very elastic sealing mat with perforated edge zones for optimum water impermeable embedding in Murexin compound seals. Chemically resistant to diluted acids, lyes, and saline solutions. System components for sealing gullies and floor outlets in conjunction with sealing systems.

#### Delivery format:

Container	Outer packaging	Pallet
750 Pcs. / Pcs.		750

#### Storage:

Can be stored frost-free, cool, and dry on wooden shelves in unopened original container: unlimited shelf life

### Processing

#### Processing:

Lay the gully seal in the fresh sealing layer and then completely rework the whole area of the edge zones with the seal. Make sure substrate is level.

### Technical data

Colour	yellow
Dimensions	500 x 500 mm (+/-5)
Thickness	1 mm (+/-0,3)

### Substrate

#### Suitable substrates:

Concrete  
Cement screed  
Anhydrite screed  
Mastic asphalt  
Plaster

40060, GULLY SEAL, valid from: 13.08.2018, Magdalena Riegler, Page 1

## Tile laying technology

Lime-cement plaster  
Masonry Gypsum  
plasterboards  
smooth concrete  
Aerated concrete  
Wooden substrates

The substrate must be dry, frost-free, solid, weight-bearing, dimensionally stable, free of dust, dirt, oil, grease, release agents, and loose parts, and it must comply with the applicable technical national and European directives, standards, and "generally accepted rules of the trade".

## Product and processing instructions

### Material information:

- When working outside the ideal temperature and/or humidity range, the material properties may change significantly.
- Bring materials up to temperature accordingly before processing!
- To retain the product properties, no foreign materials may be mixed in!
- Water dosing amounts or dilution specifications must be precisely kept!
- Check coloured products before use for colour accuracy!
- Colour consistency can only be guaranteed within a batch.
- Environmental conditions significantly influence colouring.

### Environmental information:

- Do not process at temperatures below + 5°C!
- The ideal temperature range for material, substrate, and air is +15°C to +25°C.
- The ideal relative air humidity range is between 40% to 60%.
- Increased humidity and/or lower temperatures delay and lower air humidity and/or higher temperatures accelerate drying, setting, and hardening.
- Ensure sufficient ventilation during the drying, reaction, and hardening phase; avoid draughts!
- Protect from direct sunlight, wind, and weather!
- Protect adjacent components!

### Tips:

- We recommend using a test surface first or a small area for initial, small-scale testing.
- Observe the product data sheets of all MUREXIN products used in the system.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

## Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding, and neither constitutes a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt. This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets, and the terms and conditions are available online at [www.murexin.com](http://www.murexin.com).