

## EXPANSION JOINT PROFILE HEAVY LOAD



- > suitable for higher loads
- > reduces floortension
- > top quality

### Product description

Highly load-bearing metal profile (stainless steel or aluminium) with silicone expansion joint material. For building highly mechanically load-bearing expansion joints for ceramic or natural stone coverings indoors and outdoors. This prevents cracks and damage which could occur due to increased stresses during the building phase. Moreover, this profile also reduces the propagation of body and impact noise.

#### Delivery format:

Container	Outer packaging	Pallet
3 M / Pcs.		230
3 M / Pcs.		168
3 M / Pcs.		154

#### Storage:

Can be stored frost-free, cool, and dry on wooden shelves in unopened original container: unlimited shelf life

### Processing

#### Processing:

The expansion joint profile is pressed into the prepared mortar bed. Joints from the substrate must be congruent. The stamped arm is smoothed over and the tiles are laid on both sides flush with the profile with a small joint gap. Then nothing else stands in the way of grouting.

### Technical data

Wide silicone	6 mm
Coloured silicone	grey
Total width	approx. 11.5 mm
Available heights	10, 12.5 and 15 mm

### Substrate

#### Suitable substrates:

Concrete  
Cement screed  
Anhydrite screed

44031, EXPANSION JOINT PROFILE HEAVY LOAD, valid from: 13.08.2018, Magdalena Riegler, Page 1

Tile laying technology

Mastic asphalt  
Gypsum plaster  
Lime-cement plaster  
Masonry  
Gypsum plasterboards  
smooth concrete  
Aerated concrete  
Wooden substrates

The substrate must be dry, frost-free, solid, weight-bearing, dimensionally stable, free of dust, dirt, oil, grease, release agents, and loose parts, and it must comply with the applicable technical national and European directives, standards, and "generally accepted rules of the trade".

## Product and processing instructions

Material instructions:

- The material properties may change significantly when working outside the ideal temperature and/or humidity range.
- Bring materials to correct temperature before processing!
- To retain the product properties, no foreign materials may be mixed in!
- Water addition amounts or dilution instructions must be precisely kept!
- Check coloured products before use for colour accuracy!
- Colour consistency can only be guaranteed within a batch.
- The environmental conditions significantly influence colouring.

Environmental information:

- Do not process at temperatures below + 5°C!
- The ideal temperature range for material, substrate, and air is +15°C to +25°C.
- The ideal relative air humidity range is between 40% to 60%.
- Increased humidity and/or lower temperatures delay and lower air humidity and/or higher temperatures accelerate drying, setting, and hardening.
- Ensure sufficient ventilation during the drying, reaction, and hardening phase; avoid draughts!
- Protect from direct sunlight, wind, and weather!
- Protect adjacent components!

Tips:

- We highly recommend using a test surface first or a small area for initial, small-scale testing.
- Observe the product data sheets of all MUREXIN products used in the system.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

## Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding, and neither constitutes a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt. This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets, and the terms and conditions are available online at [www.murexin.com](http://www.murexin.com).