

SPORTS FLOOR COMPLETE CARE AP 30

- > environmentally friendly
- > water-based
- > suitable for sports floors (DIN 18032)



Product description

Water-based, non-slip care agent for sealed parquet and wooden floors, sealed cork (closed pore), PVC, and linoleum. The care agent dries without polishing into a dirt-repellent, durable, and non-slip film. Indoors for initial and complete care, as well as for ongoing maintenance cleaning of parquet and all other wooden floors. Sliding friction coefficient corresponds to DIN 18032.

Delivery format:

Container	Outer packaging	Pallet
1 L /	10	280

Storage:

Can be stored for about 24 months in a frost-free, cool, and dry environment on a wooden rack in the unopened original container.

Processing

Recommended tools:

Sponge, mop, polish applicator, conventional cleaning equipment.

Processing:

Apply evenly and thinly on clean floor with the recommended tool. For initial and complete care of freshly sealed parquet and wooden floors, Sports Floor Complete Care AP 30 is applied evenly for the first time after sealing, or after each basic cleaning.

For maintenance care, a dash of Aqua Parquet Complete Care AP 20 is added to the water (0.2 - 0.3 l to 8 - 10 l mopping water) and wiped over with a well wrung sponge or mop.

Both during maintenance and basic cleaning, do not flood the floor with water, as this can cause damage due to wood swelling.

Technical data

Consumption

Dilution

Initial, complete care:

approx. 30 - 40 ml/m² (= 30 - 50 m²/l)

use as initial, complete care undiluted. as maintenance cleaner

approx. 0.2 - 0.3 l in 10 l water

Test certificates

Tested in accordance with (standard, classification ...)

DIN 18032 (Gleitreibungsbeiwert)

Substrate

Suitable substrates:

Finely polished wooden floors

Roughly hewn wooded parquet

Prefabricated parquet

The substrate must be free of dust, dirt, oil, grease, silicon, separating agents, washing residues. The requirements of the applicable standards, guidelines, and data sheets apply.

Product and processing instructions

Material information:

- The properties of the material may be significantly altered if not processed within the ideal temperature and/or humidity range.
- Bring the materials to the proper temperature before processing!
- To maintain the product properties, do not add any foreign materials!
- Water dosing quantities or dilution information must be strictly adhered to!
- Check tinted products for colour accuracy before application!
- Colour consistency can only be guaranteed within the same batch.
- The environmental conditions significantly impact colour formation.

Environmental information:

- Do not process at substrate temperatures below +15°C!
- The ideal temperature range for the material, substrate, and air is +15°C to +25°C.
- The ideal humidity range is 40% to 60% relative humidity.
- Increased air humidity and/or lower temperatures may prolong the drying, setting, and hardening time, while lower air humidity and/or higher temperatures will speed it up.
- Ensure adequate ventilation during the drying, reaction, and hardening phase; avoid draughts!
- Protect against direct sunlight, wind, and weather!
- Protect adjacent components!

Tips:

- We recommend using a test surface first or a small area for initial, small-scale testing.
- Please observe the product data sheets of all MUREXIN products used in the process.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

68091, SPORTS FLOOR COMPLETE CARE AP 30, valid from: 04.09.2018, Magdalena Riegler, Page 2

Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding and does neither constitute a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted. Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt. This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets and the terms and conditions are available online at www.murexin.com.