

PARQUET POLISH LP 35

- > protects and maintains
- > high yield
- > for floors with heavy wear



Product description

Colourless, wax- and solvent-based care agent for sealed and oiled parquet. Protects heavy wear floors sustainably and increases the lifetime of the seal.

Indoors for initial and complete care of sealed wooden floors of all types, especially for impregnated and oiled floors, parquet, boards and wood block paving.

Delivery format:

Container	Outer packaging	Pallet
1 L / BKA	10	300

Storage:

Can be stored frost-free, cool and dry on wooden shelves in the unopened original container for: 720 days

Processing

Recommended tools:

Sponge, mop, conventional cleaning equipment.

Processing:

Evenly apply to floor with suitable tools and buff with a soft cotton cloth after 5 to 10 minutes. If applied too often, the protective film becomes too thick and can form so-called traffic paths. In this case, pre-treat the floor with Murexin Basic Cleaner AP 10.

Frequency:

Load - Basic cleaning (complete care) - Maintenance cleaning Normal - 1x / year - every 8-14 days

Heavy - 1-2x / year - 2x / week

Very heavy - 2-4x / year - daily

normal ... private area (living room)

heavy ... commercial area (office)

very heavy ... public areas (schools, event halls)

Technical data

Consumption
Repolishing
Processing, environmental and
hardening temperature

Consumption/coverage per l: approx. 50 - 70 m²
after approx. 5 - 10 min.
min. +5 °C

Substrate

Suitable substrates:

all surface-treated wooden floors
finely polished wooden floors
roughly hewn wooded parquet
prefabricated parquet

The substrate must be free of dust, dirt, oil, grease, silicon, separating agents, washing residues. The requirements of the applicable standards, guidelines and data sheets apply.

For a perfect system

System products:

Aqua Basic Cleaner AP 10

Description:

Aqua Basic Cleaner AP 10 for environmentally-friendly floor and maintenance cleaning of sealed floors.

Product and processing instructions

Material information:

- When working outside the ideal temperature and/or humidity range, the material properties may change significantly.
- Temper materials accordingly before processing!
- To retain the product properties, no foreign materials may be mixed in!
- Water dosing amounts or thinning specifications must be precisely kept!
- Check coloured products before use for colour accuracy!
- Colour consistency can only be guaranteed within a batch.
- The colouring is significantly influenced by the environmental conditions.

Environmental advice:

- Do not process at temperatures below +15 °C!
 - The ideal temperature range for material, substrate, and air is +15 °C to +25 °C.
 - The ideal air humidity range is between 40% to 60%.
 - Increased humidity and/or lower temperatures delay, lower air humidity and/or higher temperatures accelerate drying, setting, and hardening.-
- Ensure sufficient ventilation during the drying, reaction, and hardening phase; avoid draughts!
- Protect from direct sunlight, wind, and weather!
 - Protect adjacent components!

Tips:

- We highly recommend using a test surface first or a small area for initial, small-scale testing.
- Observe the product data sheets of all MUREXIN products used in the system.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values that were obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding and does neither constitute a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt. This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets and the terms and conditions are available online at www.murexin.com.