

PARQUET BASIC CLEANER AP 10

- > aqueous-based
- > environmentally friendly
- > high yield



Product description

Aqueous, environmentally-friendly, easy to process cleaning agent.
Indoors for basic and intermediate cleaning of parquet and other wooden floors as well as for the removal of washing residues and hard to remove contamination.

Delivery format:

Container	Outer packaging	Pallet
1 L / KKA	10	280

Storage:

Can be stored frost-free, cool, and dry on wooden shelves in the unopened original container for: 730 days

Processing

Recommended tools:

Conventional cleaning equipment such as cloth, polish applicator.

Processing:

Distribute the cleaner evenly onto the floor and scrub manually or by machine after a short exposure time.

Frequency:

load - basic cleaning - maintenance cleaning

Normal - 1x / year - every 8-14 days

Heavy - 1-2x / year - 2x / week

Very heavy - 2-4x / year - daily

normal ... private area (living room)

heavy ... commercial area (office)

very heavy ... public areas (schools, event halls)

Technical data

Consumption

Basic cleaning: 0.1 - 0.5 litres to 1 litre of water

Intermediate cleaning: 0.1 - 0.2 litres to 10 litres of water

Substrate

Suitable substrates:

all parquet and wooden floors

For a perfect system

System products:

Aqua Parquet Complete Care AP 20, Aqua Parquet Polish LP 35

Description:

Aqua Parquet Complete Care AP 20 for initial and complete care, as well as ongoing cleaning of the parquet floor.

Aqua Parquet Polish LP 35 for initial and complete care, as well as ongoing cleaning of the parquet floor.

Product and processing instructions

Material information:

- When working outside the ideal temperature and/or humidity range, the material properties may change significantly.
- Bring materials up to temperature accordingly before processing!
- To retain the product properties, no foreign materials may be mixed in!
- Water dosing amounts or dilution specifications must be precisely kept!
- Check coloured products before use for colour accuracy!
- Colour consistency can only be guaranteed within a batch.
- Environmental conditions significantly influence colouring.

Environmental notices:

- Do not process at temperatures below +15°C!
- The ideal temperature range for material, substrate, and air is +15°C to +25°C.
- The ideal air humidity range is between 40% to 60%.
- Increased humidity and/or lower temperatures delay and lower air humidity and/or higher temperatures accelerate drying, setting, and hardening.
- Ensure sufficient ventilation during the drying, reaction, and hardening phase; avoid draughts!
- Protect from direct sunlight, wind, and weather!
- Protect adjacent components!

Tips:

- We recommend using a test surface first or a small area for initial, small-scale testing.
- Observe the product data sheets of all MUREXIN products used in the system.
- Keep a genuine original container of the respective batch for later repair work.

The information provided reflects average values obtained under laboratory conditions. Due to the use of natural raw materials, the indicated values of individual deliveries may vary slightly without impacting the product suitability.

Safety instructions

This leaflet is based on extensive experience, is intended to convey the best of our knowledge, is not legally binding and does neither constitute a contractual legal relationship nor a subsidiary obligation resulting from the bill of sale. The quality of our materials is guaranteed within the framework of our general terms and conditions. Our products may be used by professionals and/or experienced and accordingly technically skilled persons only. Users are not released from inquiring in case of uncertainties or from rendering professional workmanship. We recommend using a test surface first or a small area for initial, small-scale testing. Naturally, it is not possible to describe or foresee all possible current and future uses and peculiarities. Information that is assumed to be familiar to experts has been omitted.

Please observe the current, technical, national and European standards, guidelines and data sheets regarding materials, substrates and the subsequent construction. Please contact us if you have any reservations or doubt. This version is rendered invalid if a new version is released. The most recent data sheets, safety data sheets and the terms and conditions are available online at www.murexin.com.